



# MICRO Series

The Smallest, The Brightest

## SPECIFICATIONS

<b>Viewing Angle</b>	120° Optics
<b>Input Voltage</b>	12VDC
<b>Watts</b>	0.42w/mod (2.52w/ft.)
<b>Luminous Efficacy</b>	67 (lm/W)
<b>Modules/Foot</b>	6/ft. fully stretched
<b>Protection Grade</b>	IP65 water proof
<b>Packaging</b>	Anti-static bag, 60 modules (10 ft)/bag 40 bags/outer carton
<b>Warranty</b>	5 Year (Product) / 5 Year (Labor)
<b>Operating Temp.</b>	-40° ~ +60 °C / -40° ~ +140 °F
<b>Storage Temp.</b>	-40° ~ -70 °C / -40° ~ +158 °F
<b>Cascade</b>	40 mods single-ended power feed 80 mods double-ended power feed



- Designed for small channel letters and tight space
- UV or IR Protected
- L80 rating of 50,000 hours
- 3M double face tape and mechanical mounting options

## OPTIONS

Model	Color Temp	Lumens
G2G Micro	7500K/4200K	28 lm/mod (168lm/ft.)

\*Additional color temps available upon special order (MOQs Apply)\*

## DRAWINGS

