



WOW II


New Generation of WoW Module.

SPECIFICATIONS

Viewing Angle	170° Optics
Input Voltage	12VDC
Watts (G / B / Y)	0.72w/mod (1.08w/ft.)
(R)	0.5w/mod (0.75w/ft.)
Modules/ Foot	1.5/ft. fully stretched
Protection Grade	IP67 water proof
Packaging	Anti-static bag, 75 modules (50 ft)/bag 10 bags/outer carton
Warranty	5 Year (Product) / 5 Year (Labor)
Operating Temp.	-40° ~ +60 °C / -40° ~ +140 °F
Storage Temp.	-40° ~ -70 °C / -40° ~ +158 °F
Cascade	25 mods single-ended power feed 50 mods double-ended power feed



IP67 **us**
E344189



Transistor



3"-12" Depth Min.



5+5-Year Warranty



12VDC



L80 rating of 50,000 hours



3M Tape



UV Resistant

OPTIONS

Model	Color Temp	Lumens
WOWII White	7500K/6300K/2700K	110lm/mod (165lm/ft)
WOWII Red	Red	13lm/mod (19.5lm/ft)
WOWII Green	Green	36lm/mod (54lm/ft)
WOWII Blue	Blue	13lm/mod (19.5lm/ft)
WOWII Yellow	Yellow	36lm/mod (54lm/ft)

Additional color temps available upon special order (MOQs Apply)

- Designed for small channel letters and tight space
- UV or IR Protected
- L80 rating of 50,000 hours
- 3M double face tape and mechanical mounting options
- Custant current design

DRAWINGS

