



G2G Trident SF

A SIMPLE SOLUTION
For Sign Cabinet Lighting



SPECIFICATIONS

Luminous Efficacy	133.4 LM/W
Power	2.5W/FT
Max Mods (Series)	Full 45W load
CT	6300K/7500K
CRI	>70
LEDs Per Module	3
Protection	IP66 wet-Location
Operating Temp	-40°~ +60 °C
Warranty	7 Years
LED	SMD 2835
Packaging	30 modules per tray, 5trays per case



G2G Trident SF 160



G2G Trident SF 180



cULus **IP66**
E344189

- Constant Voltage Technology
- UV or IR Protected
- L70 rating of 50,000 hours
- 3M double face tape and mechanical mounting options

RECOMMENDED COVERAGE CHART


G2G Trident SF 160	Depth	5"	6"	7"	8"
	Spacing	8"	9"	10"	11"
G2G Trident SF 180	Depth	4"	5"	6"	7"
	Spacing	10"	12"	14"	16"

OPTIONS

Model	Voltage	Power	Current	Modules Per Ft	Lumens	Qty 60 Power Supply	Viewing Angle
G2G Trident SF 160	12VDC	3.0W/Module	250mA	1	290 Lm/Module	19 Modules	160 °
G2G Trident SF 180	12VDC	3.0W/Module	210mA	1	400 Lm/Module	19 Modules	180 °

DRAWINGS

G2G Trident SF 160



G2G Trident SF 180

